

SPECIFICATIONS



Vollay V5000 60/30 FBS 60x30mm Stile – Fixed Blade System

This system has been designed to provide the appearance of a timber shutter with the benefits that extruded aluminium offers.

The stiles are extruded aluminium, which has a 60mm wide-face and is 30mm thick and has a removal stile cover plate that allows you to install a range of 24mm thick cross rails in a 38mm, 60mm, 85mm, 110mm and 150mm width that lock into the stile shoulder.

The cross rails are assembled with stainless steel self-location screws, which are concealed within the frame and connect the suitable cross rail to suit the panel size and how it will move.

With the addition of the telescopic adjustable cross rail, this allows any panel size to be manufactured. The selected louvre, 55mm, 68mm, 90mm or 115mm aerofoil types are installed with a UV resistant nylon end cap that is located into the punched stile at the required angle and pitch.

The blades can be set at 5, 15, 30, 45 or 90 degrees angles in a range of pitches that allows the choice of a wide-range of ventilation and privacy option. The blades have the option to be locked closed with a blade lock, which is a cam design that rotates over the control rod.

A keyed lock is also can be fitted inside the stile and allows for a locking rod to pass out of both the top and bottom of the stile into the frame to secure the panel in place. The panels can be fixed, bottom roller sliding, top hung sliding, bi-folding or slide and stack provided the blades are at 5 or 15 degrees.

LOUVRES SOLUTIONS FOR ALL SEASONS



SPECIFICATIONS



Vollay V5000 60/30 FBS 60x30mm Stile – Fixed Blade System

Aluminium shall be extruded to Australian Standards AS 1866:1997.

Aluminum sections shall be powder coated to AS 3715-2002.

Aluminum sections shall be anodized to AS 1231-2000 and complies with corrosion resistance as per AS1580.457.1.

All fixings, bolts, screws and Pivots are manufactured from Stainless Steel.

All plastic parts are manufactured from UV resistant HDPP (High Density Polypropylene) or similar.

Vollay™ V5000 products are covered by our 10-year warranty against twisting, warping, sagging and surface finish failure, further, all fixings and mounded compo entry will maintain a functional level operation for the for the life of the warranty.

Please contact our office for a complete range of CAD drawings or any further assistance.

LOUVRES SOLUTIONS FOR ALL SEASONS

